


Model: ZAP 1M Series


Air Pressure Range: 80-140 psi

Settings: Up to 10,000 psi









Air Hydraulic Pump with Remote Hand Pendant

Usage:

These pumps can be found powering many different hydraulic actuators. They are a great choice when distance from the hydraulic pump or load is required for safety or the operator needs to have a better perspective of the work being performed.

Special Features:

- 1. Design based on work proven ZAP series pump.
- 2. Pressure relief valve, hydraulic pickup filter, hydraulic output filter, and air inlet filter protect pump and hydraulic components from damage.
- 3. Can be used anywhere where compressed air is available.
- 4. Pumps are built to withstand years of service and can be completely rebuilt with Zinko rebuild kits.
- 5. High fluid output utilizing minimal air input is made possible with the usage of quality lightweight internal components engineered to maximize flow rate, outperforming competitor's pumps almost two to one.
- 6. All aluminum remote hand control is lightweight and durable allowing trouble-free remote actuation of hydraulic components.
- 7. Standard ten foot pendant air hoses allow operator to control hydraulic components from a safe distance.
- 8. 1M series pumps are available in many different configurations including various sized aluminum and polyethylene reservoirs making these pumps capable of powering many types of hydraulic components.

| Model Number | Oil Capacity (in³) | Pressure Rating (psi) | Output Flow Rate (in³ / min) | | Air Pressure | Dimensions (in) | | | | | | | Oil Port | Weight |
|-----------------|--------------------------|-----------------------------|-----------------------------------|------|-----------------|-----------------|------|------|-------|------|------|------|----------|--------|
| | | | No Load | Load | Range (psi) | А | В | С | D | Е | F | G | (in) | (lbs) |
| ZAP-101-1M | 98 | 10,000 | 77 | 13 | 80-140 | 8.05 | 6.04 | 4.53 | 9.53 | 2.23 | 4.36 | 3.56 | 3/8" NPT | 20 |
| ZAP-101P-1M | 98 | 10,000 | 77 | 13 | 80-140 | 8.05 | 6.04 | 4.53 | 9.53 | 2.23 | 4.36 | 3.56 | 3/8" NPT | 19 |
| ZAP-102-1M | 183 | 10,000 | 77 | 13 | 80-140 | 8.30 | 6.29 | 4.78 | 12.00 | 2.23 | 5.63 | 3.87 | 3/8" NPT | 26 |
| ZAP-103-1M | 305 | 10,000 | 77 | 13 | 80-140 | 8.30 | 6.29 | 4.78 | 12.00 | 2.23 | 8.00 | 3.87 | 3/8" NPT | 38 |
| ZAP-103P-1M | 305 | 10,000 | 77 | 13 | 80-140 | 8.30 | 6.29 | 4.78 | 12.00 | 2.23 | 8.00 | 3.87 | 3/8" NPT | 37 |
| ZAP-104-1M | 454 | 10,000 | 77 | 13 | 80-140 | 10.63 | 8.63 | 7.11 | 10.82 | 2.23 | 9.21 | 3.59 | 3/8" NPT | 38 |